

Jolly 12

► recessed lamp ► 12 W

PROGETTO
LUCE
Made in Italy



Corpo: alluminio pressofuso
Fissaggio: molle
Montaggio: incasso
Ottica: 20° / 40° / 50°
Cavo di alimentazione: incluso 20 cm FROR antifiama 2 poli (2x0.5 mm²)
Alimentazione: 350 mA
Potenza massima assorbita: 12 W
Temperatura di utilizzo: -30°C + +50°C
Peso:
Normativa: prodotti in conformità alle vigenti norme Europee

Body: die-cast aluminum
Fixing: springs
Installation: recessed
Optics: 20° / 40° / 50°
Power supply cable: cable 20 cm FROR fireproof 2 pole (2x0.5mm²)
Power supply: 350 mA
Maximum absorbed power: 12 W
Working temperature: -30°C + +50°C
Weight:
Norms: products comply European norms



Colori standard
Standard colour



Bianco
White

Colorazione riflettore intercambiabile
Interchangeable reflector color



Nero
Black



Grigio
Grey



Bianco
White



Pink gold
Oro rosa



Oro
Gold



RoHS



Colorazione LED standard
Standard LED coloration



Bianco
White
3200°K



Luce per gioielli
Light for jewels
4200° K



Importante!

La temperatura del metallo in prossimità del LED non deve superare il valore di 50°C.

Remarks!

The temperature of the metal near the LED should not exceed 50°C.

Codici :
Code :

Lenti / Lens	20°	40°	50°
Bianco / White	JLY12 20 B	JLY12 40 B	JLY12 50 B



Dissipazione
Passiva
Dissipation
Passive



Lumen
+/- 1840Lm/mt
Massima Potenza
Max Power



CRI > 90 - 97



Speciiche LED
120 lm/W
LED type
120 lm/W



Dimmerabile
Si
Dimmable
Yes



Garanzia
Jolly 12: 3 anni
Alimentatore: 2 anni
Warranty
Jolly 12: 3 years
Power supply: 2 years



Disegno tecnico
Technical drawing

