

Towering

► h 350 mm

► recessed lamp

► 5 W

PROGETTO
LUCE 
Made in Italy 



Corpo: metallo verniciato

Fissaggio: su superficie (pannello con foro passante)

Montaggio: incasso

Ottica: riflettore in PMMA 50°

Cavo di alimentazione: cavo 50 cm in dotazione

Alimentazione: tensione 350 mA (± 5%)

Potenza massima assorbita: 5 W

Temperatura di utilizzo: -30°C + +50°C

Peso: 120 gr

Normativa: prodotti in conformità alle vigenti norme Europee

Body: painted metal

Fixing: surface (panel with hole)

Installation: recessed

Optics: reflectors in PMMA 50°

Power supply cable: 50 cm cable included

Power supply: voltage 350 mA (± 5%)

Maximum absorbed power: 5 W

Working temperature: -30°C + +50°C

Weight: 120 gr

Norms: products comply European norms



Colori standard
Standard colors



Bianco
White



Grigio
Grey



Nero
Black

Altri colori RAL a richiesta
Other RAL colors on request

Finiture disponibili
Finishes available



Ottone satinato
Satin brass



Ottone lucido
Polished brass



Ottone brunito
Brunished brass



Nikel satinato
Satin nickel



Cromo lucido
Polished chrome



RoHS



Colorazione LED standard
Standard LED coloration



Bianco
White
5500°K



Bianco
White
3200°K



Luce per gioielli
Light for jewels
4200°K



Importante!

La temperatura del metallo in prossimità del LED non deve superare il valore di 50°C.

Remarks!

The temperature of the metal near the LED should not exceed 50°C.

Codici Pikk
Code Pikk

Lenti/Lens	50°
Nero / Black	TWRG N 50
Bianco /White	TWRG B 50
Grigio / Grey	TWRG G 50
Ottone Satinato / Satin Brass	TWRG OS 50
Ottone Lucido / Polished Brass	TWRG OL 50
Ottone Brunito / Brunished Brass	TWRG OB 50
Nikel Satinato / Satin Nikel	TWRG NS 50
Cromo Lucido / Polished Chrome	TWRG CL 50



Dissipazione
Passiva
Dissipation
Passive



Garanzia
Towering: 3 anni
Alimentatore: 1 anno
Warranty
Towering: 3 years
Power supply: 1 year



Lumen
+/- 400 Lm



IRC/CRI > 90 - 97



Dimmerabile
No
Dimmable
No



Disegno tecnico
Technical drawing

